

# T5565B 2S PLUS TILT-TOWER

TYRE CHANGER

John Bean.



# **TILT-TOWER**TYRE CHANGER



#### MH 330 PRO

Comprised of a new bead pressing tool with lifting hook, hex roller, top roller, and lifting disk, the new MH 330 PRO streamlines the mounting and demounting of low-profile and high-performance tyres, enabling a single technician to perform tasks with ease.



#### **ADJUSTABLE CLAMPING JAWS**

Compact turntable for a smaller footprint with three-way adjustable, self-centring clamping jaws that accommodate a 10 to 26-inch rim diameter and a minimised cylinder stroke for faster clamping.



#### **PROspeed™**

The innovative self-adjusting technology provides the optimum torque and maximises the rotation speed for safe, efficient operation.



#### **ON-FLOOR BEAD BREAKER**

Ergonomic pedal-operated bead breaker with five shovel adjustment axes for precision placement. High pad offset keeps the tyre and turntable cylinder free from interference.

# **EXPANDED SERVICE CAPABILITIES**PERFORMANCE AND PRECISION





#### **FLEXION GUARD**

The tilt-tower provides high rigidity with a reinforced horizontal arm that prevents flexions of the system when working on run-flat and high-performance tyres.

#### "PLUS" CONFIGURATION

Certified by WDK, the "Plus" models are equipped with Pneumatic Bead Assist and "Plus" Accessories Kit to enable correct mounting and demounting of UHP and run-flat tyres.

#### PNEUMATIC VERTICAL ARM

Fast and ergonomic, the pneumatic vertical arm facilitates positioning of the mounting head on all wheels.

#### **WDK CERTIFIED**

Our tyre changers are approved and certified according to the strict and rigorous guidelines of the prestigious Wirtschaftsverband der deutschen Kautschukindustrie e.V. (WDK).

#### **TOP-SIDE BEAD SEATER**

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.

#### **TOOL BOX**

The tool box provides a fixed storage area with four convenient shelves for tools, valves, and accessories, with an integrated air pressure gauge.

#### **NEW PRESSING TOOL**

The updated MH 330 pro pneumatic bead assist features a new pressing foot style optimised to prevent tool slippage that could damage tyres and wheels.

#### **LOW-PROFILE CABINET**

The chassis height is two inches lower than standard tyre changers to provide increased ergonomics when working with large wheels.





## **T5565B 2S PLUS**

### **TECHNICAL SPECIFICATIONS**

Max Rim Diameter	26"   66cm
Max Tyre Width	15"   38cm
Max Wheel Diameter	44"   112cm
Power Supply	230V 1ph 50-60Hz 15A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	72"x63"x67"   182x159x171cm

<sup>\*</sup>Additional models & configurations are available.

### STANDARD ACCESSORIES

- Wave Lever Plus
- Wave Lever Plus Protector
- 5 kg Lube Bucket Holder
- Lube Brush
- Plastic Protectors for Mounting
- Jaw Protectors Front & Rear
- Plastic Tyre Protector
- Rim Protection and String
- Bead Breaker Blade Protector
- "Plus" Kit

### **OPTIONAL ACCESSORIES**

- Quick Exchange Device with Mounting Head
- Bead Breaker Blade for Off-Road Wheels
- Wheel Lift
- MH Tractor Kit
- 4" Jaws Adaptors
- · Light Truck Adaptor
- · Motorcycle Accessories



FIND A DISTRIBUTOR





